

ALLER single lamp, twin lamp or triple lamp

Energy-efficient luminaire mounting rail system for easy installation and maintenance

IP 54 CE protection class I
pending

ALLER



Form retaining, corrosion resistant aluminium profile, dust repellent, easy to clean for complete removal of dirt and residue (hygienic), with a maximum modular length of 4590 mm (luminaire inserts 1230 mm to 1530 mm). Available in six profile versions.

Normally, the distance between the pendants is approx. 2.5 m. Depending on the profile and load, they can be adjusted to approx. 6.0 m. For special lengths, please specify the desired pendant distance and expected line load in your order. Luminaire inserts with multi-watt ECG. The mounting rails are pre-fitted with 7 x 2.5 mm² through wiring as standard. This allows for a wide range of switching options without any additional installation effort. Profile 4 is supplied with 2 x 7 x 2.5 mm² through wiring. It therefore caters for the easy integration of additional circuits, safety lighting elements and lighting control devices.

With luminaire adapters and factory pre-set luminaire connecting points according to planning scheme. Supplied as complete system ready for installation.

Easy and quick lamp service thanks to NORKA-Rapid-mounting pressure cap. Luminaire inserts with up to three lighting points and reflector tubes that can be swivelled by max. 120° (protection against dirt). The system is also suitable for use under HACCP or GMP conditions in the food processing/pet food industry (e.g. shatter protection).

