

NORKA Luminaire BERLIN single and twin lamp

IP 65        for compact fluorescent lamps



Compact luminaire BERLIN


Housing: PC anthracite (fracture proof), lamp cover PC clear (fracture proof), inside ribbed

Electronics: low loss ballast and starter or electronic ballast ready for connection, 4 cable entries

Mounting: 2 sealed openings on the back side

Gaskets: silicone-/synthetic rubber, non-ageing, form-retaining

Reflector: wide beam



Version/Wattage	Order no.	Lamp holder	Weight approx. kg	Version	Order no.
-----------------	-----------	-------------	-------------------	---------	-----------

Luminaire BERLIN – standard version –

with lamp cover PC clear (fracture proof), inside ribbed

TC-EL 1 x 9/11 HF	421 070	2 G 7	1,2
TC 1 x 9/11 ind.	421 110	G 23	1,2
TC-L 1 x 18 ind.	421 180	2 G 11	1,6
TC-D 1 x 18 ind.	421 190	G 24 d-2	1,6
TC-D 1 x 26 ind.	421 260	G 24 d-3	1,5
TC-L 1 x 18 HF	421 270	2 G 11	1,3
TC 2 x 9 ^{*)} ind.	422 050	G 23	1,2
TC-EL 2 x 9/11 ^{*)} HF	422 070	2 G 7	1,5
TC 2 x 9/11 ind.	422 110	G 23	1,6
TC-L 2 x 18 ^{*)} ind.	422 150	2 G 11	1,7
TC-L 2 x 18 ^{*)} HF	422 170 ¹⁾	2 G 11	1,6
TC-L 2 x 18 ind.	422 190	2 G 11	2,4

Luminaire BERLIN without lamp cover

TC-EL 1 x 9/11 HF	421 07V	2 G 7	
TC 1 x 9/11 ind.	421 11V	G 23	
TC-L 1 x 18 ind.	421 18V	2 G 11	
TC-D 1 x 18 ind.	421 19V	G 24 d-2	
TC-D 1 x 26 ind.	421 26V	G 24 d-3	
TC-L 1 x 18 HF	421 27V	2 G 11	
TC 2 x 9 ^{*)} ind.	422 05V	G 23	
TC-EL 2 x 9/11 ^{*)} HF	422 07V	2 G 7	
TC 2 x 9/11 ind.	422 11V	G 23	
TC-L 2 x 18 ^{*)} ind.	422 15V	2 G 11	
TC-L 2 x 18 ^{*)} HF	422 17V ¹⁾	2 G 11	
TC-L 2 x 18 ind.	422 19V	2 G 11	

^{*)} Tandem circuit

¹⁾ only for outdoor use

Luminaire BERLIN for recessed mounting with lamp cover

PC clear (fracture proof), inside ribbed, with straight housing sides

TC-L 1 x 18 ind.	421 280	2 G 11	
TC-L 1 x 18 HF	421 370	2 G 11	
TC-L 2 x 18 ind.	422 280	2 G 11	

Luminaire BERLIN with lamp cover PC clear (fracture proof), internal reflector, asymmetric beam

TC-L 1 x 18 ind.	421 200	2 G 11	
TC-L 1 x 18 HF	421 470	2 G 11	

Accessories and additional prices

Lamp cover PC clear
(fracture proof), inside ribbed **500 731**

Lamp cover PC opal white
(fracture proof) **500 751**

Lamp cover PC clear
(fracture proof) **500 732**

Lamp cover
straight housing sides,
PC clear (fracture proof), inside ribbed **500 742**

Lamp cover PC (fracture proof)
– red **500 733**
– blue **500 734**

Wall bracket
stainless steel **200 207**

Angle bracket
stainless steel **200 208**





Ceiling mounting bracket
– for pannel ceiling **203 222**
– for closed ceiling **203 221**

Housing in version
– grey **421 961**
– transparent **421 962**

Anti-vibration mounting brackets
for special mounting applications **421 004**

Compensation
– 1 x 18 W **421 022**
– 2 x 18 W **422 022**

Luminaire **BERLIN** single and twin lamp

IP 65     for compact fluorescent lamps



Light – in compact design –

